

SUPER PLASTICIZER FLOWAID FT

Admixture for GRC Production

Product Name Product Type Uses **Polycarboxylic** Super-plasticizing **FLOWAID FT Admixture for Sprayed GRC** Polymer/Lignosulphonate Uses Particularly suitable for sprayed premix and sprayed GRC Enables large water reductions to be made whilst retaining workability. **Advantages** High workability without segregation No retardation Up to 20% water reduction possible Can be used with acrylic polymer **Method of Use** Dispense with mix water Dosage 0.5 – 1.5% by weight of cement – Confirm after trials Storage and Shelf Life Minimum 1 year in sealed containers stored in dry warehouse conditions $(5 - 30^{\circ}C)$ PROTECT FROM FROST **Properties** Appearance: Brown Liquid Specific Gravity: 1.06 Chloride content % w/w: <1.10% Chloride Free Effect on setting: Little effect

SUPPLIED IN 25L, 200L AND 1000L IBC'S SUPPLIED BY FIBRE TECHNOLOGIES INTERNATIONAL

+1°C

All Portland Cements

For further information contact:

Freezing point °C

Suitability:

Fibre Technologies International Limited
Avonmouth Way
Avonmouth
Bristol BS11 9YA

E: +44 (0)117 9825855
Fax: +44 (0)117 9820060
info@fibretech.org
www.fibretech.org



