

# BUBBLE GUM

## LIQUID RELEASE



**THE CLEAR BUBBLEGUM LR ALLOWS FOR TEXTURING AND REMOVAL OF TEXTURE MAT WHILE LEAVING THE IMPRINT INTACT. WITH A SLIGHT BUBBLE GUM ODOR AND A LONGER OPEN TIME, BUBBLEGUM LR IS THE RELEASE AGENT FOR THE 21ST CENTURY.**

### PRODUCT HIGHLIGHTS

- **With a Flash Point over 140° F:** Bubblegum LR is much safer to handle and to store, and it is much safer to work with because it contains no hazardous aromatic solvents.
- **Controlled evaporation:** With a slower evaporation rate, there is more open time. Much less time wasted re-spraying forms or re-working areas because stamps dry out and stick.
- **Transparent:** The clear, colorless release will not stain concrete or forms.
- **Non-volatile:** Bubblegum LR is not volatile. Nothing is left behind to stain or affect the surface of the finished concrete. Forms dry clean and ready to use again.
- Bubblegum Liquid Release Contains no aromatic solvents and no chlorinated solvents that are environmentally harmful.
- **Available in 1 gallon and 5 gallon.**

### USES

Bubblegum Liquid Release is used to provide a clean release for all stamping operations and is also excellent as a release agent on concrete forms.

### QUICK LOOK:

**Type:** Bubble Gum LR solvent release agent  
**Toxicity:** Low  
**VOC's:**  
**Flammability:** Combustible  
**Composition:** Highly Hydrorefined aliphatic solvent release  
**Color:** Pale Blue  
**Odor:** Bubble Gum  
**Coverage:**  
*\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,  
PLEASE SEE SDS.



# BUBBLE GUM LIQUID RELEASE

## **HOW TO USE:**

Apply Bubblegum LR with a pump up type sprayer. Apply to surfaces at the rate of 200 ft<sup>2</sup> per gallon for concrete, and 175 ft<sup>2</sup> per gallon for polymer overlays.

1. Spray the tools. Usually one coat is sufficient.
2. Spray the surface to be stamped. Only cover an area that can be stamped in approximately 20 minutes, or a second application may be required.
3. Allow the floor to stand open for several hours. The Bubblegum LR will evaporate. Never trowel Liquid Release into the fresh concrete.  
\* Bubblegum LR contains no hazardous aromatic solvents, and with a flash point greater than 142°F (61°C), it poses a far lower safety hazard than common liquid release agents and without the mess of powders. This is particularly important with interior applications.

## **PRECAUTIONARY STATEMENT:**

Keep away from away from open/hot surface. No smoking. Wear protective gloves/eye protection/face protection. Store locked up in a well-ventilated place. Keep cool. Dispose of contents/container according to local, state and federal regulations.

## **FIRST AID:**

IF INGESTED: Do not induce vomiting. Get Immediate Medical Help. Never give any liquids by mouth to an unconscious person.

IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

IF INHALED: Remove to fresh air.

IF ON SKIN: Rinse off thoroughly with water then soap and water. Wash contaminated clothing before reuse.

## **IN CASE OF FIRE:**

This product is combustible. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.

## **FOR PROFESSIONAL USE ONLY**