

Technical Datasheet - METYX Composite Reinforcements

PRODUCT CODE	5200.013.005	
PRODUCT NAME	CW600 B-CARBON 12K 2X2 TWILL WOVEN-100CM	
PRODUCT DESCRIPTION		
CUSTOMER CODE		
CUSTOMER ID		

	REINFORCEMENT CONSTRUCTION					
	LAYER	FIBER TYPE	AREA WEIGHT			
1	Warp	800 Tex - 12K Carbon	300 gr / m2			
2	Weft	800 Tex - 12K Carbon	300 gr / m2			
3						
4						
5						
6						
7						

* Checked via own test based on ISO 3374.

TOTAL* 600 gr / m2 (±%5)

OTHER PROPERTIES		ROLL INFO	
Stitch Gauge		Roll Width	100 cm
Stitch Type		Roll Weight	30 kg
Stitch Length		Roll Length	50 m
Pilot Yarn / Position		Core Diameter	76 mm

Resin Compatibility	Loss on Ignition	Moisture Content
Polyester, Vinylester, Epoxy resins	-	-

Packaging	All rolls are wrapped with polyethylene bags; placed in pallet boxes or in single cardboard boxes or in pyramid style on pallets.	
Labelling	Each roll is labelled on the inner side of the core, on the bag or on the cardboard boxes including a unique reference number for its traceability.	
Storage	age Store at %40-70 relative humidity and 18-30 °C temperature range. Recommended to be brought to working area 24 hrs prior to use.	

Certification	DNV	Lloyd's Register
Metyx products are produced by Telateks A.S. company	TYPE Approved	
who is run by ISO 9001:2008 QA System.		

Note: The above specifications reflect the product data on release date but are subject to change without prior notice.

Address:

Orhanli Beldesi 34956 Tuzla Istanbul – TURKIYE



 Phone:
 +90-216-394-32-60

 Fax
 :
 +90-216-394-32-58

 Web
 :
 www.metyx.com